

SAP DESCRIPTION:

NC 360508 C

SKU No.

Maximum Flow Rate: 1100 GPM

Recommended Flow Rate: 880 GPM


Inlet Pressure: 115 PSI

Sheet Size:

A4

Scale:

1:30



**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED


Designed By: KEREM 03/05/2021

Drawn By: KEREM 03/05/2021

Checked By:

QA

Sheet: 1 Of: 3 Rev. -



SAP DESCRIPTION:

NC 360508 C

SKU No.

Maximum Flow Rate: 1100 GPM

Recommended Flow Rate: 880 GPM


Inlet Pressure: 115 PSI

Sheet Size:

A4

Scale:

1:30



**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED.

Designed By	KEREM	03/05/2021
-------------	-------	------------



Drawn By	KEREM	03/05/2021
----------	-------	------------

Checked By		
------------	--	--

QA		
----	--	--

Sheet: 2	Of: 3	Rev. -
----------	-------	--------

ITEM NO.	SAP Description	SAP Cat. No.	QTY.
1	SANDSTORM NC TANK 36"X3" VIC	71920-003200	5
2	PE MAN 6"*3 OUT*3" VIC F/36" TANK	71920-002050	2
3	PE MAN 6"*2 OUT*3" VIC F/36" TANK	71920-002040	2
4	PE BF MAN 3"*3 OUT*2" VIC F/36" TANK	71920-002010	1
5	PE BF MAN 3"*2 OUT*2" VIC F/36" TANK	71920-002000	1
6	PE CAP 6"VIC W/1 OUT 3/4"BSP+2 OUT 2"BSP	71920-002489	1
7	PE CAP 6" VIC W/1 OUT 3/4" BSP	71920-002490	3
8	METAL TRANSITION 8" ANSI FLANGE*VIC	71910-002012	2
9	PE STUB END 3" W/O FLANGE	71920-002300	1
10	3"CAP WITH VACUUM BREAKER		1
11	METAL TEE CON 8*6*8 VIC L-420MM	71910-002300	2
12	METAL NIPPLE VIC/VIC 3"*420MM	71910-009000	1
13	DOROT BF valve 3"*2"*3" vic vic vic	71600-006590	5
14	3" THROTTLE VALVE FLANGED TYPE F/BF MAN	71920-000100	1
15	VICTAULIC COUPLING 2" ONE BOLT	71910-002500	5
16	VICTAULIC COUPLING 3" ONE BOLT	71910-002501	19
17	VICTAULIC COUPLING 6" TWO BOLT	71910-002503	8
18	VICTAULIC COUPLING 8" TWO BOLT	71910-002504	2
19	LOOSE FLANGE PP ANSI 90X3"	75090-012405	1
20	S75PL H 2" QRV NPT PP 3WNC R	71600-002338	1
21	Plastic Nipple 2" BSP	75090-012457	1
22	Control stand + controller + Aquative bracket		1
23	CONTROL KIT FOR MEDIA FILTER - BSP	37090-009600	1
24	L.P. Check point (part of control kit)		3
25	BARAK PLASTIC BASE 2 GD-010(NPT)	70561-001500	1
26	SUPPORT LEG 6"X1440 FOR NC	71920-003030	2
27	SUPPORT LEG 3"X1180 FOR NC	71920-003000	2
28	SUPPORT LEG 6"X410 FOR NC	71920-003020	4



SAP DESCRIPTION:

NC 360508 C

SKU No.

Maximum Flow Rate: 1100 GPM

Recommended Flow Rate: 880 GPM


Inlet Pressure: 115 PSI

Sheet Size:

A4

Scale:

1:30



**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED

Designed By: KEREM 03/05/2021

Drawn By: KEREM 03/05/2021

Checked By:

QA

Sheet: 3 Of: 3 Rev. -