

LITE MANUAL DISC FILTERS

**SAME QUALITY DEPTH
FILTRATION AT A LOWER COST**



2" Dual Lite



3" Twin Lite

PRODUCT ADVANTAGES

- Polypropylene components for increased chemical resistance.
- Easy opening plastic clamp for access to the discs.
- Redesigned spine threads firmly into the body for easier reassembly after cleaning.
- Highly effective multiple disc ring design captures and holds more debris.

APPLICATIONS

- Primary irrigation filter for relatively clean or average water quality
- Protection of irrigation systems from clogging and/or abrasion
- Block or zone filter for large field applications
- House or zone filter for greenhouse and nursery applications
- Primary filter for a small commercial landscape or wastewater application with good or average water quality

SPECIFICATIONS

- Maximum Recommended Working Pressure: 115 psi
- Flow Range:
2" Dual: 1 - 110 GPM
3" Twin: 1 - 220 GPM
- Connections:
2" Dual - Male Threaded
3" Twin - Flanged (removable flange converts to grooved connection)
- Dimensions:
2" Dual - 16 5/16" Length, 10 1/4" Width, 6.6 lbs.
3" Twin - 28 3/4" Length, 9 14/32" Width, 17 lbs.

ORDERING INFORMATION

ITEM NUMBER	MODEL NUMBER	SIZE	MESH
70640-004523	25A2DL-040	2" DUAL	040
70640-004522	25A2DL-080	2" DUAL	080
70640-004521	25A2DL-120	2" DUAL	120
70640-004520	25A2DL-140	2" DUAL	140
70640-006777	25A3TL-040F	3" TWIN	040
70640-006780	25A3TL-080F	3" TWIN	080
70640-006783	25A3TL-120F	3" TWIN	120
70640-006786	25A3TL-140F	3" TWIN	140

MESH/MICRON

MESH	040	080	120	140
MICRON	400	200	130	115
RING COLOR	Blue	Yellow	Red	Black



NETAFIM USA
5470 E. HOME AVE.
FRESNO, CA 93727
CS 888 638 2346
F 800 695 4753
www.netafimusa.com