








TECHLINE® DRIPLINE COMPARISON



	TECHLINE COPPER				TECHLINE HCVXR-RW & RWP				TECHLINE CV XR				TECHLINE CV				TECHLINE DL				TECHLINE RW & RWP				TECHLINE EZ							
	ROOT INTRUSION PROTECTION				ROOT INTRUSION PROTECTION				SMALL & MEDIUM AREAS				MAXIMUM UNIFORMITY				MAXIMUM UNIFORMITY				RECYCLED/ RECLAIMED WATER				SMALL & MEDIUM AREAS							
Emitter Flow Rate (GPH)	0.33	0.53	0.77		0.33	0.53	0.77		0.42	0.61	0.92		0.26	0.42	0.61	0.92		0.26	0.42	0.61	0.92		0.26	0.42	0.61	0.92		0.26	0.42	0.61	0.92	
Tubing Color																																
DIAMETER	17mm				17mm				17mm				17mm				17mm				17mm				12mm							
APPLICATION: TURF	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SHRUB & GROUND COVER	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
INSTALLATION: SUBSURFACE	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
ON-SURFACE	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
AIR/VACUUM RELIEF VENT REQUIRED FOR SUBSURFACE?	No	No	No		No	No	No		No	No	No		No	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
EMITTER SPACING: 6"	S.O.*				S.O.*				S.O.*				S.O.*				S.O.*				S.O.*											
12"	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
18"	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
24"	Yes	Yes	Yes		Yes	Yes	Yes		No	No	No		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	S.O.*							
BUILT-IN CHECK VALVE	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	No	No	No	No	S.O.*				No	No	No	No				
ANTI-SIPHON EMITTER	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
PRESSURE COMPENSATING	21.8 to 58 psi				21.8 to 58 psi				14.5 to 58 psi				14.5 to 58 psi				6 to 58 psi				6 to 58 psi				6 to 58 psi							
CONTINUOUS SELF-FLUSHING EMITTERS	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
MAXIMUM RECOMMENDED SYSTEM PRESSURE	58 psi				58 psi				58 psi				58 psi				58 psi				58 psi											
MINIMUM PRESSURE REQUIRED	21.8 psi				21.8 psi				14.5 psi				14.5 psi				6 psi				6 psi				6 psi							
BENDING RADIUS	7"				7"				7"				7"				7"				7"				6"							
QUALIFIES FOR LEED CREDIT	Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
USE WITH RECLAIMED WATER	No				No - HCVXR Yes - HCVXR-RW/RWP				No				No				No				Yes				No							
MAXIMUM LENGTH OF SINGLE LATERAL (FEET) @ 45 PSI, 18" EMITTER SPACING	663	488	381		663	488	381		620	489	371		845	620	489	371	1019	750	591	450	1019	750	591	450	533	392	308	234				
FLOW PER 100 FEET, 18" EMITTER SPACING (GPH)	22.0	35.3	51.3		22.0	35.3	51.3		28.2	40.5	61.6		17.6	28.2	40.5	61.6	17.6	28.2	40.5	61.6	17.6	28.2	40.5	61.6	17.6	28.2	40.5	61.6				

*Note: Special Orders (S.O.) can be placed to accommodate custom spacing or other special considerations. Set-up charge, higher pricing and longer leadtimes may apply.



netafimusa.com



**DOWNLOAD OUR
LANDSCAPE & TURF
CATALOG APP**

