
NetBow™ Container Irrigation Multi-Outlet Dripping Arc

Installation Manual



© COPYRIGHT 2021, NETAFIM™

NO PARTS OF THIS PUBLICATION MAY BE REPRODUCED, STORED IN AN AUTOMATED DATA FILE OR MADE PUBLIC IN ANY FORM OR BY ANY MEANS, WHETHER ELECTRONIC, MECHANICAL, BY PHOTOCOPYING, RECORDING OR IN ANY OTHER MANNER WITHOUT PRIOR WRITTEN PERMISSION OF THE PUBLISHER.

ALTHOUGH NETAFIM[™] TAKES THE GREATEST POSSIBLE CARE IN DESIGNING AND PRODUCING BOTH ITS PRODUCTS AND THE ASSOCIATED DOCUMENTATION, THEY MAY STILL INCLUDE FAULTS.

NETAFIM[™] WILL NOT ACCEPT RESPONSIBILITY FOR DAMAGE RESULTING FROM USE OF NETAFIM'S PRODUCTS OR USE OF THIS MANUAL.

NETAFIM[™] RESERVES THE RIGHT TO MAKE CHANGES AND IMPROVEMENTS TO ITS PRODUCTS AND/OR THE ASSOCIATED DOCUMENTATION WITHOUT PRIOR NOTICE.

In the event that you are reading this manual in a language other than the English language, you acknowledge and agree that the English language version shall prevail in case of inconsistency or contradiction in interpretation or translation.




Specs. & Recommendations

- Compatible with 10-60 liters (2.5-15 gallon) containers
- Diameter: 120, 250 mm (5, 10 inches)
- Dripping outlets: 8 and 4 respectively.

The flow from each one of the dripping outlets is the hub dripper flow divided by the number of dripping outlets.

- Minimum operating pressure: according to hub dripper definitions.
- Maximum recommended pressure at the hub dripper inlet: 4.0 bar (58 PSI)
- Flow of the hub dripper should be 2.0-8.0 l/h (0.53-2.11 GPH).
 If your required flow / pressure is out of this range, consult your Netafim[™] local representative.




Connection options

Netbow[™] can be connected to different hub dripper - PCJ, PC, or UniRam[™] with Dr. Zip[™]


• When connected to a hub dripper, NetBow[™] can deliver flow rate as low as ¼ I/h from each one of its 4 or 8 dripping outlets, while maintaining sufficient velocity for self-cleaning.

NetBow[™] options of hub dripper



Installation

- Cut a section of 3X5 mm diameter micro-tube at the required length to reach conveniently from the hub dripper to the NetBow[™] inlet. Using SSPE (super soft polyethylene) micro-tube is recommended for ease of installation (pre-cut SSPE micro-tube sections of the required length with the required assembly fittings can be ordered).
- Connect it to the barb connector of the hub dripper. If the hub dripper is fitted with a Press-Fit outlet connector, use a Press-Fit to barb adapter (see available options on page 5).



NetBow[™] options of connection to the hub dripper


PCJ on line

PCJ with barb outlet



 PCJ with Press-Fit outlet and straight Press-Fit to barb adaptor • PC with Press-Fit outlet and straight Press-Fit to barb adaptor


PC on line




• PC with Press-Fit outlet and elbow Press-Fit to barb adaptor




• UniRam[™] with Dr. Zip[™] and straight Press-Fit to barb adaptor




• UniRam[™] with Dr. Zip[™] and elbow Press-Fit to barb adaptor




• PCJ with Press-Fit outlet and elbow Press-Fit to barb adaptor









6 different NetBow[™] models are offered


- 250mm/10" with insertable spikes;
- 250mm/10" with foldable spikes;
- 120mm/5" with foldable spikes,

each with barb or Press-Fit connector (See Product order data on page 8)

NetBow™ models with foldable spikes


• Extend the 5 foldable spikes on the NetBow™ underside

Size	Outlets	Connector	Spikes
250mm/10"		Barb	Insertable
250m/10"	0	Press-Fit	Insertable
250mm/10"	8	Barb	
250mm/10"		Press-Fit	Foldable
120mm/5"	4	Barb	Foldable
120mm/5"	4	Press-Fit	




NetBow[™] models with insertable spikes

 Insert the 5 spikes into the 5 holes on the NetBow[™] underside




Continue installation (all models)

- Connect the free side of the micro-tube to the NetBow[™] barb inlet.
 For NetBow[™] with Press-Fit inlet use a straight Press-Fit to barb adaptor
- Place the NetBow[™] on the the substrate surface in the pot, surrounding the plant location.
- Insert the NetBow[™] spikes into the substrate so that its underside is in contact with the substrate.



• Adjust the NetBow[™] inlet T orientation (up/down) as to allow the optimal micro-tube position.



Order Details

Product order data

Product Descritption	Quantity per box (Units)	Box sizes (Inches)	Box weight (lb)	Boxes per pallet	Cat. No.
NetBow™ 250mm/10", 8 outlets, barb, grey	60		11.5		77470-000106
NetBow™ 250m/10", 8 outlets, Press-Fit, grey	00				77470-000124
NetBow™ 250mm/10", 8 outlets, barb, grey, foldable	50 L	W 22 I 11	11	24	77470-000125
NetBow™ 250mm/10", 8 outlets, Press-Fit, grey, foldable		H 12.5	11	24	77470-000126
NetBow™ 120mm/5", 4 outlets, barb, grey, foldable	120		13		77470-000142
NetBow™ 120mm/5", 4 outlets, Press-Fit, grey, foldable					77470-000143

Accessories

The NetBow[™] can be connected directly by micro-tube to Netafim[™] PCJ on line drippers equiped with a barb outlet, or to PC, PCJ on line drippers and UniRam[™] integral driplines with Dr. Zip[™], using one of the following Netafim[™] adapters (to be ordered separately):

Product	Descritption	Units	Cat. No.
Micro-tube	Inlet: Female Press-Fit	1 unit	32000-001950
Adapter barb - straight	Outlet: Barb, 3 X 5	50 units/bag	N/A
3 X 5	Colored gray	100 units/bag	N/A
Micro-tube	Inlet: Female Press-Fit	1 unit	32000-002000
Adapter barb - straight	Outlet: Barb, 3 X 5	50 units/bag	32000-002010
3 X 5	Colored brown	100 units/bag	32000-002020
Micro-tube	Inlet: Female Press-Fit	1 unit	N/A
Elbow adapter barb 3 X 5	Outlet: Barb, 3 X 5	50 units/bag	32000-002520
	Colored black	100 units/bag	32000-002525
Micro-tube	Inlet: Female Press-Fit	1 unit	N/A
Elbow adapter barb 3 X 5	Outlet: Barb, 3 X 5	50 units/bag	32000-002526
	Colored gray	100 units/bag	N/A
Soft PE micro-tube		100 m length	40005-000202
	Soft PE micro-tube bi-layer, gray outside, black inside	200 m length	40005-000201
		500 m length	40005-000200

Related assemblies

Product name	Descritption	Functionality	Units*	Cat. No.
SR W/OD MEL-FPF SSG-0.60M	Press-Fit Elbow Adapter Gray + 60cm SSG Microtube	To connect Press-Fit hub dripper to NetBow™ barb		40200-043275
	Straight Adapter Black + 60cm SSG Microtube	To connect Press-Fit hub dripper to NetBow™ barb	1	40200-043276
SR PCJH-4LH-BRB W/OM SSG-0.60M	PCJ HCNL 4 L/H + 60cm SSG Microtube	PCJ + micro tube to connect PE pipe to NetBow™ barb		40200-046499

*The catalog number is in units but orders will be in boxes of 500 units

For more information about Netafim's drippers see the drippers catalog at http://www.netafim.com/irrigation-products-technical-materials.

Author: Abed Masarwa, Product Management Dept., March 2020

8 | **NETBOW™** INSTALLATION MANUAL

ASSEMBLIES

Model Number	Descritption	Units*
11002520-B	5mm Elbow	50
11WPCON-B	3mm flex tube adapter (for nipple outlet drippers)	250
15FPEW53-18	18" Pre-cut Super flex uv white pe tubing (5/3 mm)	100
15FPEW53-24	24" Pre-cut Super flex uv white pe tubing (5/3 mm)	100
15FPEW53-30	30" Pre-cut Super flex uv white pe tubing (5/3 mm)	100
15FPEW53-36	36" Pre-cut Super flex uv white pe tubing (5/3 mm)	100

GROW MORE WITH LESS WWW.NETAFIMUSA.COM

NETBM 01/22