

SAP DESCRIPTION:

PLS SNG 481212 H

SKU No.

Maximum Flow Rate: 4490 GPM

Recommended Flow Rate: 3700 GPM


Inlet Pressure: 115 PSI

Sheet Size:

A4


Scale:

1:50



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED

Designed By		
Drawn By	KEREM	05/11/2020
Checked By		
QA		
Sheet: 1	Of: 3	Rev. -



SAP DESCRIPTION:

PLS SNG 481212 H

SKU No.


Maximum Flow Rate: 4490 GPM

Recommended Flow Rate: 3700 GPM

Inlet Pressure: 115 PSI

Sheet Size:
A4


Scale:
1:50



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED

Designed By		
Drawn By	KEREM	05/11/2020
Checked By		
QA		
Sheet: 2	Of: 3	Rev. -

ITEM NO.	SAP Description	SAP Cat. No.	QTY.
1	SANDSTROM NC TANK 48"X4" VIC	71920-003210	12
2	PE MAN 8"*2 OUT*4" VIC F/48" TANK	71920-002070	8
3	PE MAN 8"*1 OUT*4" VIC F/48" TANK	71920-002060	8
4	PE BF MAN 4"*2 OUT*3" VIC F/48" TANK	71920-002030	4
5	PE BF MAN 4"*1 OUT*3" VIC F/48" TANK	71920-002020	4
6	INLET MANIFOLD F/NC H SYS 12X10X8 2605mn	71920-004101	1
7	OUTLET MANIFOLD F/NC H SYS 12X10X8 885mm	71920-004100	1
8	PE STUB END 4" W/O FLANGE extended	71920-002305	2
9	METAL TRANSITION 12" ANSI FLANGE*VIC	71910-002019	2
10	PE CAP 4" VIC	71920-002405	2
11	PE CAP 8"VIC W/1 OUT 3/4"BSP+2 OUT 2"BSP	71920-002508	4
12	PE CAP 8" VIC W/1 OUT 3/4" BSP	71920-002509	4
13	METAL NIPPLE VIC/VIC 4"*460MM	71910-009010	2
14	DOROT BF valve 4"*3"*4" vic vic vic	71600-006595	12
15	4" THROTTLE VALVE FLANGED TYPE F/BF MAN	71920-000110	2
16	VICTAULIC COUPLING 3" ONE BOLT	71910-002501	12
17	VICTAULIC COUPLING 4" ONE BOLT	71910-002502	48
18	VICTAULIC COUPLING 8" TWO BOLT	71910-002504	24
19	VICTAULIC COUPLING 12 TWO BOLT	71910-002506	2
20	LOOSE FLANGE PP ANSI 110X4"	75090-012415	2
21	S75PL H 2" QRV NPT PP 3WNC R	71600-002338	4
22	Plastic Nipple 2" BSP	75090-012457	4
23	Control stand + controller + Aquative bracket		2
24	1" CONTROL KIT FOR MEDIA FILTER - NPT	37090-009610	2
25	L.P. Check point (part of control kit)		4
26	BARAK PLASTIC BASE 2 GD-010(NPT)	70561-001500	4
27	SUPPORT LEG 8"X1440 FOR NC	71920-003050	4
28	SUPPORT LEG 8"X410 FOR NC	71920-003040	12
29	SUPPORT LEG 4"X1180 FOR NC	71920-003010	4



SAP DESCRIPTION:

PLS SNG 481212 H

SKU No.

Maximum Flow Rate: 4490 GPM

Recommended Flow Rate: 3700 GPM


Inlet Pressure: 115 PSI

Sheet Size:

A4

Scale:

1:40



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NETAFIM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NETAFIM IS PROHIBITED

Designed By

Drawn By

KEREM

05/11/2020

Checked By

QA

Sheet: 3

Of: 3

Rev. -