# Elevate HIGH POWER

Elevate yield and other crop characteristics with the industry's highest performing spectrally tunable grow light. Whether growing flowers, vegetables, fruit or medicinal plants, the Elevate product family will help deliver more from the plants with less power, risk & resource consumption.





Flexible, Modular Design



Installation



**User-Friendly** 

### Benefits & Features

- Industry-leading Photosynthetic Efficacy
- Compatible with standards-based wired and wireless controls
- Multiple Spectrum options
- Sub-Canopy & Side-Lighting
   Options boost yield beyond
   canopy saturation
- Quick connect wire harnesses for Plug-and-Play installation
- Rope ratchet or Aircraft cable mounting options

### / Elevate Specifications High Power

- + PPE (µmol/J): > 2.8
- + PPF: > 2200 3700
- + PPFD: 1000 2000 Typ.
- + Recommended Coverage Area:
  - 4' x 4' single unit 6- to 10-bar
  - 4' x 5'+ single unit 8- to 15-bar
- + Power Supplies: Dim-to-Off, Programmable
- + Testing / Certification: UL / DLC
- + Warranty (System): 5 years
- + Warranty (Driver): 7 years (@ < 75°C)
- + Fixture Dimensions/Weight:


Max 45" x 60" x 5" (drivers on-board) @ 45 lbs Max 45" x 60" x 3" (drivers remote) @ 33 lbs

\* x: number of bars



#### **Spectrum Power Distribution**

TWO CHANNELS TOGETHER OR INDEPENDENTLY CONTROLLED



orbia

Grow Lights High Powe						
Product	Description	Units	Part No.	Component Details		
Vertical Flower	15-Bar High Performance Spectrum Tunable Bloom Light	16 units/ pallet	Elevate-15F	Fully assembled; Ready to mount; See included accessories below		
Vertical Vegetative Grow Light	8-Bar High Performance Veg Light	16 units/ pallet	Elevate-8V	Fully assembled; Ready to mount; See included accessories below		
Single Bar Grow Light X 1	Top or In Canopy (Single Bar Only)	8 units/ count	SC1-T-ECO BO	Light Bar Only 24VDC Constant Current		
Subcanopy Grow Light x 4	Subcanopy Fixture (4 Bar w/ Driver and cords)	16 units/ pallet	SC4PLUS	Order AC and DC cables separately		

#### **Grow Light Accessories**

Туре	Part No.	Description	Included Elevate-xF	Included Elevate-xV
AC Power Cabling	AC4D	AC Daisy Chain (4 Light)		
AC Power Cabling	ACWJ	AC Quick Connect to Flying Leads (1 Light)		
AC Power Cabling	ACEX10	AC Extension (10' cable)		
AC Power Cabling	ACTC	AC Quick Connect Tee	1	1
AC Power Cabling	ACN6-15P	AC Cable and Plug NEMA 6-15P	1	1
DC Control Cabling	DC-5	DC 1-to-5 Splitter	у	у
DC Control Cabling	DCex10	DC Extension (10' cable)		
DC Control Cabling	DS5	DC Daisy Chain (2-Pin) (4 Driver)		
DC Control Cabling	FLS	Mini Quick Connect to Flying Leads	1	1
DC Control Cabling	ZGA1	Integrated Zhaga Connector (for DC Control)	2	1
Mounting	YYR2	Nylon mountring rope ratchets (2 pc pack)	2	2
Controls	SPTRUWIFI	SpecTru Spectral Sensor w/ Wifi		
Controls	BLETDL	Bluetooth Adapter for up to 40 Drivers		
Controls	MAN10	Rotary Manual (0-10) Dimmer		

## Electrical Specs

- Industrial UL Class P
   (Type HL) Programmable
   LED Driver
- + Input Voltage: 90~305Vac
- + Power Range (LED) for Vegetative:

400W - 640W

+ Power Range (LED) for Flowering:

1000W - 1300W

+ Total Input Current (Amps):
3.6 -4.7A @ 277V
4.2 - 5.5A @ 240V

8.3 - 11.0A @ 120V

- + Efficiency: 93%+
- + Built-in Active PFC Function > 98% @ Full load
- + Dimming Function: 0.5V-10V, Dim-to-Off
- Reliability Protection: OVP,
   SCP, OTP, and 10KV Surge
   Protection
- + Safety Regulation: UL8750, UL8800 & EN61347, DLC
- + Waterproof Rating: IP66



