PIPE & TUBING



POLYETHYLENE TUBING



PRODUCT ADVANTAGES

- Made from the highest quality low density resins.
- Excellent Ultra-Violet (UV) and acid resistance.
- Available in black or bright white color, standard coil lengths or large diameter reels to meet your specific needs.
- Bright white tubing is opaque to prevent algae growth, withstand heat and harsh chemicals while producing cooler water temperatures.
- Every reel undergoes a battery of tests to insure high quality manufacturing standards are met.
- Available with pre-punched holes at various spacings.

POLYETHYLENE TUBING ACCESSORIES



VINELINE CLIP Pre-installed Adjustable Clip

Easily adjustable - clip moves from one end of the tubing to the other preventing water migration. Economical option saves labor. Available for tubing with .670", .780" or .790" outside diameters.



ON-LINE DRIPPERS Pressure Compensating or Non-Compensating

Designed with a large flow path allowing particles to pass freely through for long-term efficient operation. Can be installed anywhere along the tubing. Available in pressure compensating or non-compensating options with multiple flow rates.



FINEST LOW DENSITY POLYETHYLENE RESIN AVAILABLE

APPLICATIONS

- Tree, vine, permanent row crop and greenhouse or nursery
- Subsurface, surface and suspension from vine
- For use with riser lines

NETAFIM OFFERS THE INDUSTRY'S LONGEST WARRANTY

Blank Polyethylene Tubing is warranted to be free from original defects in materials and workmanship for a period of seven (7) years and ten (10) years for environmental stress cracking (surface or subsurface applications). This warranty applies only to products with a wall thickness of 35 mil or greater.

AGRICULTURAL APPLICATIONS





PE Tubing with On-Line Drippers in Vineyard

PE Tubing with SuperNet Sprinkler in Orchard

GREENHOUSE & NURSERY APPLICATIONS



PE Tubing with On-Line Drippers in Nursery



PE Tubing with Multi-Outlet Drippers for Containers

POLYETHYLENE TUBING

ORDERING AND TECHNICAL INFORMATION - BLACK POLYETHYLENE TUBING									
NOMINAL INSIDE	DIAMETER OUTSIDE	NOMINAL WALL THICKNESS	NOMINAL DIAMETER (MM)	COIL Length	MAXIMUM WORKING PRESSURE (psi)	MODEL NUMBER			
0.400″	0.490"	0.045″	10.2 x 12.5	1,000′	75	14040049			
0.520″	0.620"	0.050″	13.2 x 15.8	500′	66	14052062-05			
0.520″	0.620″	0.050″	13.2 x 15.8	1,000′	66	14052062			
0.520″	0.630"	0.055″	13.2 x 16.0	1,000'	72	14052063			
0.570″	0.660"	0.045″	14.5 x 16.8	500′	55	14057066-05			
0.570″	0.660"	0.045″	14.5 x 16.8	1,000′	55	14057066			
0.600″	0.700″	0.050″	15.2 x 17.8	500′	58	14060070-05			
0.600"	0.700"	0.050"	15.2 x 17.8	1,000′	58	140060070			
0.620″	0.710″	0.045″	15.8 x 18.0	500′	51	14062071-05			
0.620″	0.710″	0.045″	15.8 x 18.0	1,000'	51	14062071			
0.690″	0.790″	0.050″	17.5 x 20.1	1,000'	51	14069079			
0.700″	0.800"	0.050″	17.8 x 19.96	500′	50	14070080-05			
0.700″	0.800"	0.050″	17.8 x 20.3	1,000′	50	14070080			
0.720″	0.820"	0.050″	18.3 x 21.1	1,000′	49	14072082			
0.720″	0.830"	0.055″	18.3 x 21.3	1,000'	53	14072083			
0.720″	0.840"	0.060"	18.8 x 21.3	1,000'	58	14072084			
0.740″	0.840"	0.050″	18.8 x 21.3	1,000'	48	14074084			
0.820″	0.930″	0.055″	20.8 x 23.6	500′	47	14082093			
0.820″	0.930"	0.055″	20.8 x 23.6	1,000'	47	14082093-1000			
0.820″	0.940″	0.060"	20.8 x 23.9	500′	51	14082094			
0.820″	0.940″	0.060"	20.8 x 23.9	1,000′	51	14082094-1000			
0.830″	0.940″	0.055"	21.1 x 23.9	500′	46	14083094			
0.830″	0.940"	0.055″	21.1 x 23.9	1,000′	46	14083094-1000			
1.060″	1.200″	0.070″	26.9 x 30.5	250′	47	14106120-25			
1.060″	1.200″	0.070″	26.9 x 30.5	500′	47	14106120			

ORDERING AND TECHNICAL INFORMATION - BRIGHT WHITE POLYETHYLENE TUBING										
NOMINAI INSIDE	DIAMETER OUTSIDE	NOMINAL WALL THICKNESS	NOMINAL DIAMETER (MM)	COIL Length	MAXIMUM WORKING PRESSURE (psi)	MODEL NUMBER				
0.520″	0.620″	0.050″	13.2 x 15.8	500′	66	14BW052062-05				
0.520″	0.620"	0.050"	13.2 x 15.8	100′	66	14BW052062-01				
0.600″	0.700″	0.050″	15.2 x 17.8	500′	58	14BW060070-05				
0.600"	0.700"	0.050″	15.2 x 17.8	100′	58	14BW060070-01				
0.700″	0.800″	0.050″	17.8 x 20.3	1,000'	50	14BW070080				
0.700″	0.800″	0.050″	17.8 x 19.96	500′	50	14BW070080-05				
0.820″	0.940″	0.060"	20.8 x 23.9	100′	51	14BW082094-01				
1.060″	1.200″	0.070″	26.9 x 30.5	100′	44	14BW106120-01				

NOTE: Select sizes are available in other coil lengths. Not all products listed in these charts are stocking items. Non-stock products are subject to a minimum order quantity. Call Netafim USA Customer Service for additional details.



NETAFIM USA 5470 E. HOME AVE.

FRESNO, CA 93727 CS 888 638 2346 www.netafimusa.com