


ITEM NO.	SAP Description	SAP Cat. No.	QTY.
1	METAL SNG.CHA.PLUS 48"*4" VIC PN08 LONG	71910-001626	6
2	METAL MAN 8"*2 OUT*4" VIC F/48" TANK	71910-001713	6
3	METAL BF MAN 4"*2 OUT*3" VIC F/48" TANK	71910-001712	3
4	MET CUP 8"VIC W/2 OUT 2"NPT +1 OUT 1"NPT	71910-001804	2
5	METAL CUP 4" VIC	71910-001792	1
6	NET METAL B.F VALVE 4X3 STRAIGHT VIC	71600-006660	6
7	VICTAULIC COUPLING 3" ONE BOLT	71910-002501	6
8	VICTAULIC COUPLING 4" ONE BOLT	71910-002502	22
9	VICTAULIC COUPLING 8" TWO BOLT	71910-002504	8
10	Control stand + controller + Aquative bracket		1
11	1" CONTROL KIT FOR MEDIA FILTER - NPT	37090-009610	1
12	L.P. Check point (part of control kit)		1
13	BARAK PLASTIC BASE 2 GD-010(NPT)	70561-001500	1
14	SUPPORT LEG 8"-150MM	71910-001916	4
15	SUPPORT LEG 4"-1400MM	71910-001952	1





SAP DESCRIPTION:

MTL SNG 480608 S


SKU No.

Maximum Flow Rate: 2244 GPM
Recommended Flow Rate: 1848 GPM

1:40

Inlet Pressure: 115 PSI
Sheet Size: Scale:

A4





PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
NETAFIM. ANY REPRODUCTION IN PART
OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF NETAFIM IS PROHIBITED

esigned By	KEREM	3.10.2022
rawn By	KEREM	3.10.2022
Checked By		
QΑ		
Sheet: 3	Of: 3	Rev